

GM-EST. FUEL ECONOMY

City	15 mpg (manual) 13 mpg (automatic)
Highway	22 mpg (manual) 23 mpg (automatic)

FUEL TANK CAPACITY

18.5 gal. / 70 liters

ENGINE

Type:	LT5 6.2L Supercharged V-8 with direct and port injection
Bore & stroke (in / mm):	4.06 x 3.62 / 103.25 x 92
Block material:	Cast aluminum
Cylinder head material:	Cast aluminum
Valvetrain:	Overhead valve, two valves per cylinder
Fuel delivery:	Direct and port injection
Horsepower (hp @ rpm):	755 @ 6300 rpm (SAE certified)
Torque (lb.-ft. @ rpm):	715 @ 4400 rpm (SAE certified)

TRANSMISSION & AXLE

Type:	7-speed manual with Active Rev Match 8-speed paddle-shaft automatic
Final Drive Ratio:	3.42 (manual) 2.41 (automatic)

CHASSIS & SUSPENSION

Front Suspension:	Short/long arm (SLA) double wishbone, cast aluminum upper and lower control arms, transverse-mounted composite spring, Magnetic Selective Ride Control
Rear Suspension:	Short/long arm (SLA) double wishbone, cast aluminum upper and lower control arms, transverse-mounted composite spring, Magnetic Selective Ride Control
Steering Type:	Variable-ratio rack-and-pinion with electric power assist
Turning Circle (ft. / m):	39.2 / 11.6
Brake Type:	Front and rear power-assisted discs with two-piece carbon ceramic matrix rotors; fixed six-piston aluminum front calipers and fixed four-piston aluminum rear calipers
Brake Rotor Size (in / mm):	Front –15.5 / 394 Rear –15.3 / 388
Wheel Size:	Front: 19-inch x 10.5-inch

	Rear: 20-inch x 12-inch
Tire Size:	Michelin Pilot Super Sport run-flat (std.) Michelin Pilot Sport Cup 2 (ZTK) Front: P285/30ZR19 Rear: P335/25ZR20

EXTERIOR DIMENSIONS

Wheelbase (in. / mm):	106.7 / 2710
Overall Length (in. / mm):	176.9 / 4493
Overall Width (in. / mm):	77.4 / 1965
Overall Height (in. / mm):	48.6 / 1234
Track (in. mm):	63.6 / 1615 (front) 62.5 / 1588 (rear)

INTERIOR DIMENSIONS

Headroom (in / mm):	38 / 962
Legroom (in. / mm):	43 / 1092
Shoulder Room (in. / mm):	55 / 1397
Hip Room (in. / mm):	54 / 1371

WEIGHTS & CAPACITIES

Curb Weight (lb. / kg):	3524 / 1598
EPA passenger volume (cu. ft. / L):	52 / 1472
Cargo volume (cu. ft. / L):	15 / 425